





**Manufacturer** WestWood® Kunststofftechnik GmbH

**Product Name** Wecryl 276


### Product Rating

- The product fulfills the requirements for paints and coatings and contribute to achieve one LEED credit within IEQ Credit 4.2.
- The product fulfills the requirements for Flooring Systems and contribute to achieve one LEED credit within IEQ Credit 4.3.

### Indoor Environmental Quality (IEQ) - LEED Category

IEQ Credit 4.1: Low Emitting Materials: <b>Adhesives and Sealants</b>	1 Point	
IEQ Credit 4.2: Low Emitting Materials: <b>Paints and Coatings</b>	1 Point	
IEQ Credit 4.3: Low Emitting Materials: <b>Flooring Systems</b>	1 Point	
IEQ Credit 4.4: Low Emitting Materials: <b>Composite Wood and Agrifiber Products</b>	1 Point	

### Materials and Resources (MR) - LEED Category

MR Credit 4: <b>Recycled Content</b>	1-2 Points	
MR Credit 5: <b>Regional Materials</b>	1-2 Points	
MR Credit 6: <b>Rapidly Renewable Materials</b>	1 Point	
MR Credit 7: <b>Certified Wood</b>	1 Point	






### Product Characteristics

Wecryl 276 is a fast-reactive, PMMA-based primer used as a barrier on absorbent substrates in preparation for the later application of WestWood waterproofing or surfacing products.

### About LEED & Products - [www.usgbc.org](http://www.usgbc.org)

This declaration helps to assess products easily according the certification system LEED® 2009 New Construction and Major Renovations NC & CS (excluded SCHOOLS). Products are not reviewed or certified by LEED. LEED credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information about LEED visit [www.usgbc.org/leed](http://www.usgbc.org/leed). The project team or the manufacturer is responsible to declare the compliance with the project requirements to achieve LEED points.

Below you find an explanation of the symbols. Detailed information are on the next pages.

-  **Credit requirements fulfilled - the credit point can be achieved**
-  **Credit is not applicable to this product**
-  **X% of the product comply with the credit requirement**
-  **Required data not specified - for required data contact manufacturer**
-  **Credit requirements are not fulfilled**

**Manufacturer**                      **WestWood® Kunststofftechnik GmbH**
**Product Name**                      **Wecryl 276**

Detailed Rating	Product Name	Manufacturer	Mass per unit* [%]	VOC in g/l	VOC-Limit in g/l	Flooring Systems	Composite Agrifiber product	Recycled Content		Regional Materials		Rapidly Renewable Material	Certified Wood
								Post-Consumer	Pre-Consumer	Location Harvesting/ Extraction	Location Manufacturing		
A1	Wecryl 276	WestWood® Kunststofftechnik GmbH	~ 100%	0	100	Low-VOC sealer/ finish/ stain	N/A	Not specified	Not specified	Not specified	Petershagen (D)	Not specified	N/A
A2													
A3													
A4													
A5													
A6													
A7													
A8													
A9													
A10													
	<b>Wecryl 276</b>	<b>WestWood® Kunststofftechnik GmbH</b>	<b>100.0</b>	✓	✓	✓	○	—	—	If the location of 'Harvesting & Extraction' and 'Manufacturing' is within a radius of 500 miles of the project the subproduct contributes to the credit.		—	○

\*All values are based on the unit: \*\*LEED default recycled content for steel

**Manufacturer**      **WestWood® Kunststofftechnik GmbH**

**Product Name**      **Wecryl 276**

**IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants (1 Point)**

**Intent**

Reduce the quantity of indoor air contaminants that are odorous, irritating and/or harmful to the comfort and well-being of installers and occupants caused by adhesives and sealants applied on site.

**Requirement**

All adhesive, sealants and sealant primers used on the interior of the building (defined as inside of the weatherproofing system and applied on-site) must comply shall comply with the VOC content limits of the following:

- SCAQMD Rule #1168 (effective date of July 1, 2005 and rule amendment date of January 7, 2005),
- Aerosol Adhesives must comply with Green Seal Standard for Commercial Adhesives GS-36 requirements in effect on October 19, 2000.

**IEQ Credit 4.2: Low Emitting Materials: Paints and Coatings (1 Point)**

**Intent**

Reduce the quantity of indoor air contaminants that are odorous, irritating and/or harmful to the comfort and well-being of installers and occupants caused by paints and coatings applied on site.

**Requirement**

Paints and coatings used on the interior of the building (defined as inside of the weatherproofing system and applied on-site) must comply with the VOC content limits of the following:

- Green Seal Standard GS-11, Paints Edition, May 20, 1993,
- Green Seal Standard GC-03, Anti-Corrosive Paints, Second Edition, January 7, 1997, and
- South Coast Air Quality Management District (SCAQMD) Rule 1113, Architectural Coatings, rules in effect on January 1, 2004.

**Detailed Rating**

No	Product Name	Manufacturer	Related Credit	Product Type	VOC-Content		Contribution of Product	
					Allowable	Product		
A1	Wecryl 276	WestWood® Kunststofftechnik GmbH	IEQ Credit 4.2	Quick-dry Primers, Sealers and Undercoaters	100g/l	0g/l	The product fulfills the requirements for paints & coatings.	✓

**Manufacturer**      **WestWood® Kunststofftechnik GmbH**

**Product Name**      **Wecryl 276**

**IEQ Credit 4.3: Low Emitting Materials: Flooring Systems (1 Point)**

**Intent**

Reduce the quantity of indoor air contaminants that are odorous, irritating and/or harmful to the comfort and well-being of installers and occupants caused by carpets and other hard surface flooring.

**Requirement**

- All carpet must meet the testing and product requirements of the Carpet and Rug Institute Green Label Plus program,
- all carpet cushion must meet the requirements of the Carpet and Rug Institute Green Label program,
- all carpet adhesives must meet the VOC-limit of 50g/l according to IEQ Credit 4.1,
- all hard surface flooring must be certified as compliant with the FloorScore standard (current as of the date of this rating system, or more stringent version) by an independent third-party,
- concrete, wood, bamboo and cork floor finishes such as sealer, stain and finish must, meet the requirements of SCAQMD Rule 1113 (January 1, 2004),
- tile setting adhesives and grout must meet SCAQMD Rule 1168 (July 1, 2005) VOC limits correspond.

**Detailed Rating**

No	Product Name	Manufacturer	Product Type	Testing requirement/ Certificate	Contribution of Product
A1	Wecryl 276	WestWood® Kunststofftechnik GmbH	Sealer/Stain/Finish	Quick-dry Primers, Sealers and Undercoaters (SCAQMD Rule 1113)	The product fulfills the requirements for floor finishes such as sealer, stain and finish for low-emitting flooring systems.



**Manufacturer**      **WestWood® Kunststofftechnik GmbH**

**Product Name**      **Wecryl 276**

**MR Credit 4: Recycled Content (1-2 Points)**

**Intent**

To increase demand for building products that incorporate recycled content materials, thereby reducing impacts resulting from extraction and processing of virgin materials.

**Requirement**

Use materials with recycled content\* such that the sum of post-consumer\*\* recycled content plus one-half of the pre-consumer\*\*\* content constitutes at least 10%/20% (based on cost) of the total value of the materials in the project.

The minimum percentage materials recycled for each point threshold is as follows:

- 10% Recycled Content -> 1 Point
- 20% Recycled Content -> 2 Points.

\* Recycled content is defined in accordance with the International Organization of Standards document, ISO 14021 — Environmental labels and declarations — Self-declared environmental claims (Type II environmental labeling).

\*\* Postconsumer material is defined as waste material generated by households or by commercial, industrial and institutional facilities in their role as end-users of the product, which can no longer be used for its intended purpose.

\*\*\* Preconsumer material is defined as material diverted from the waste stream during the manufacturing process. Reutilization of materials (i.e., rework, regrind or scrap generated in a process and capable of being reclaimed within the same process that generated it) is excluded.

**Detailed Rating**

No	Product Name	Manufacturer	Recycled Content		Contribution of Product
			Post-Consumer	Pre-Consumer	
A1	Wecryl 276	WestWood® Kunststofftechnik GmbH	Not specified	Not specified	No recycled content specified.

**Manufacturer**      **WestWood® Kunststofftechnik GmbH**

**Product Name**      **Wecryl 276**

**MR Credit 5: Regional Materials (1-2 Points)**

**Intent**

To increase demand for building materials and products that are extracted and manufactured within the region, thereby supporting the use of indigenous resources and reducing the environmental impacts resulting from transportation.

**Requirement**

Use building materials or products that have been extracted, harvested or recovered, as well as manufactured, within 500 miles of the project site for a minimum of 10% or 20%, based on cost, of the total materials value. If only a fraction of a product or material is extracted, harvested, or recovered and manufactured locally, then only that percentage (by weight) must contribute to the regional value. The minimum percentage regional materials for each point threshold is as follows:

- 10% Regional Materials -> 1 Point
- 20% Regional Materials -> 2 Points.

**Detailed Rating**

No	Product Name	Manufacturer	Location Harvesting/ Extraction	Location Manufacturing
A1	Wecryl 276	WestWood® Kunststofftechnik GmbH	Not specified	Petershagen (D)

**Manufacturer**      **WestWood® Kunststofftechnik GmbH**

**Product Name**      **Wecryl 276**

**MR Credit 6: Rapidly Renewable Materials (1 Points)**

**Intent**

To reduce the use and depletion of finite raw materials and long-cycle renewable materials by replacing them with rapidly renewable materials.

**Requirement**

Use rapidly renewable building materials and products for 2.5% of the total value of all building materials and products used in the project, based on cost. Rapidly renewable building materials and products are made from plants that are typically harvested within a 10-year or shorter cycle.

**Detailed Rating**

No	Product Name	Manufacturer	Rapidly Renewable Material	Percentage	Contribution of Product
A1	Wecryl 276	WestWood® Kunststofftechnik GmbH	Not specified	Not specified	No data is specified.